



FLUJÓMETRO



NCM-603



ESPECIFICACIONES TÉCNICAS

Transmitter

- Technology..... Ultrasonic Transit Time
- Enclosure..... Handheld
High impact thermoplastic
Nema 3. (7.9" x 3.6" x 1.3")
- Accuracy..... +/- 1 to 2% of rate for liquids
with velocities >0.5 fps
- Power:..... 3 AAA NiH built in batteries,
Rechargeable batteries
10 hrs of operation.
USB power charger
- Keypad..... Data Entry
- Display..... 2 lines Digital LCD, Flow Rate,
Totalizer and Diagnostics.
- Units..... English and metrics, flow rate
- Totalizer..... Net, Pos & Neg.
- Data Logger 2,000 lines of data & software
- Flow Range..... 0.1 to 20 FPS
Bi-directional
- Temp..... 32° F to 176° F (0° to 80°C)

Transducer NCM-M1

- Type..... Pair of Clamp-on 1 MHz
transducers, 15 ft of cable.
- Pipe Size..... 2" to 28" (50 to 700mm)
- Pipe Material..... Metal, most plastics
- Liquid Type..... Liquids with < 1% suspended
solids or aeration. Requires a
full pipe.
- Mounting Kit..... Magnetic rail, Mounting
straps,
(F-100-100) Silicone Acoustic
mounting compound.
- Temperature..... 32° F to 176° F (0° to 80°C)





Oceanografía

Meteorología

Drones/RPAS

Hidrografía

Topografía



Solicita tu cotización y visítanos en:

<https://www.oceanproo.net>

Ubícanos en:

Av. Las Palmeras N° 5334
Los Olivos 15304

